

TECHNICAL DATASHEETS



Safety sandals

- 4.5 mm studs for maximum grip on all flooring
- Self-fastening straps for a closer fit
- Two-fabric upper: for a sharper look
- Reflective insert at the heel for better visibility



COMPOSITION

* Weight per shoe

Upper	Suede split			
Linning	Textile			
Toe Cap	Polycarbonate			
Stay clean insole	Textile and EVA Foam. Removable.			
Puncture proof insert	Non-metallic			
Sole	Double density PU/PU			
Weight for size 37*	420g			
Weight for size 42*	550g			





The sole design supports the natural arch of the foot for greater comfort and less tiredness in an upright position.




An exclusive technology that absorbs the impact for you and provides greater comfort day in day out.



An encapsulated air bubble absorbs the micro-impacts of walking.

DRY AND RISK FLOOR • NORM: EN ISO 20345: 2011



P Antipuncture sole

SRC Antislip sole**

E Shock-absorption

A Antistatic

FO Oil and fuel resistant shoe





**	COEFFICIENT OBTAINED	FLAT		HEEL	
	FOR SIZE 42	NORM	PARADE	NORM	PARADE
	SRA Antislip Ceramic / Nals (soap solution)	0,32	0,37	0,28	0,34
	SRB Antislip steel / Glycerine (oil)	0,18	0,27	0,13	0,14