

TECHNICAL DATASHEETS



Micro-aerated safety shoes

- A fit known for its ergonomic style, guaranteeing good posture
- Three-fabric upper for an adventurer style
- Wide metallic loops for easy tightening



COMPOSITION

| Upper | Suede split |
|--|--|
| Linning | Textile |
| Toe Cap | Steel |
| Stay clean insole | Felt. Removable. Antibacterial. Antifungal. |
| Sole | Double density PU/PU |
| Weight for size 42* * Weight per shoe | 600g |





The sole design supports the natural arch of the foot for greater comfort and less tiredness in an upright position.



An exclusive technology that absorbs the impact for you and provides greater comfort day in day out.



An encapsulated air bubble absorbs the micro-impacts of walking.

DRY AND REGULAR FLOOR • NORM: EN ISO 20345: 2011

| S | Toe cap (200J) |
|----------|-----------------------------|
| SRC | Antislip sole** |
| E | Shock-absorption |
| A | Antistatic |
| FO | Oil and fuel resistant shoe |

| ** | COEFFICIENT OBTAINED | FLAT | | HEEL | |
|----|--|------|--------|------|--------|
| | FOR SIZE 42 | NORM | PARADE | NORM | PARADE |
| | SRA Antislip Ceramic / Nals (soap solution) | 0,32 | 0,35 | 0,28 | 0,33 |
| | SRB Antislip steel / Glycerine (oil) | 0,18 | 0,29 | 0,13 | 0,18 |